TSQ-2060DIP

FEATURES

Wide Frequency range.

High shock tolerance.

Small size.

Reliable frequency stability.

Pb-free and RoHS/Green compliant.



APPLICATIONS


Permits use as a clock source for communication equipment, AV equipment, OA equipment, measuring instruments and various of clocks.

S P E C I	F I C A T I O N S
Holder Type	Tuning Fork 2060
Frequency Range	30KHz to 200KHz
Frequency Tolerance (△F) (at25°C)	±10ppm to ±30ppm
Parabolic curvature constant	-0.042 ppm / (\triangle °C) 2 Maximum
Q - factor	50000 Minimum
Operating Temperature Range	-10°C -+60°C
Storage Temperature Range	-40°C - +85°C
Aging (25℃)	±5ppm/ year Maximum
Shunt Capacitance (C0)	1.0PF Typical, 2pF Maximum
Motional Capacitance (C1)	2.5fF Typical
Drive Level	1μW Maximum
Insulation Resistance (Rs)	500 Mega ohms Minimum at D.C100V
Load Capacitance (CL)	Suggested by customer

EQUIVALENT SERIES RESISTANCE	(ESR) AND MODE OF OPERATION
Frequency Range	$\mathrm{ESR}(\Omega)$
$30.000 \text{KHz} \le f < 40.000 \text{KHz}$	40KMax
$40.000 \text{KHz} \le f < 60.000 \text{KHz}$	30KMax
$60.000 \text{KHz} \le f < 70.000 \text{KHz}$	25KMax
70.000 KHz \leq f < 100.000 KHz	22KMax
$100.000 \text{KHz} \le f < 200.000 \text{KHz}$	20KMax


Mechanical Dimensions

10.00MAX



Unit: mm

Frequency vs. Temperature Curve



Note: Specification are subject to change without notice. For more detail and update, please visit our website.